

SOLID F64

THE MICROPLEX SOLID F64 is a versatile, easy-to-use continuous form laser printer. The **F64** printer is a new generation print engine that offers a small footprint and provides the user with flexible media management capabilities, by utilizing two independent pin-fed tractor cassettes, the intelligent Paper Stacker (iPS) and an integrated Cutting device.

Handling media widths of up to 18 inches wide, the **F64** is perfectly suited for decentralized, network-based environments, supporting industries such as **banking, mailing, insurance, fulfillment services, health services, distribution and logistics**. The multipurpose **SOLID F64** is also capable of printing MICR (CMC7 and E13B) and is **PIRA** certified. The optional intelligent Paper Stacker (iPS) assures stacking of forms up to 3,000 pages without operator involvement.

FEATURES

63 pages/minute print speed (two-up letter)

2-Up support for Letter and A4 format,
18" media width

300,000 pages/month duty cycle

Two different fanfold media paths,
alternatively accessible

Integrated Paper Cutter for print job separation

Low Power Consumption

Optional intelligent Paper Stacking (iPS)
without operator involvement



APPLICATIONS

Distribution and Logistics

Banking

Mailing

Insurance

Fulfillment Services

Health Services

MICR Applications for E13B and CMC7

PIRA Certified



MICROPLEX[®]

Toll Free: 877.99SOLID
www.MICROPLEX-USA.com

SPECIFICATIONS

Technology	Electrophotography (LED Array), OPC Drum and Heat/Pressure Fuser
Print Speed	63 ppm (letter, 2-Up); 41 ppm (letter, landscape); 31ppm (11" form length)
Resolution in dpi	300x300
Recommended Monthly Print Volume	300,000 pages (letter, 2-Up)
Power Supply	110 V (-10/+6%) 50-60 Hz or 220V (-10/+6%) 50-60Hz
Dimensions in inches	35W x 30.7D x 13.8H (inclusive tractor cassettes)
Weight	247 lbs (without iPS CF50)

ELECTRICAL/NOISE LEVEL

Power Consumption	12A @ 110-120V
Operating Wattage	less than 1200 Watt average; less than 1650 Watt maximum
Power Save Mode	less than 45 Watt
Standby Mode	less than 100 Watt

PAPER HANDLING

Input	Two independent, detachable tractor cassettes for fanfold paper
Output Options	Integrated cutting device separates print jobs; Optional iPS CF50 stacker
Media Size	3"-24" length without stacker, 7"-17" if attached to stacker; 6"-18" width (print area 17")
Media Weight	17 to 41 lb continuous fanfold media



BARCODES

Linear	UPC A, UPC E, Code 39, USPS Postnet and Intelligent Mail Barcode (IMB) (Planet Code, 4-State), EAN 8, EAN 8+ Add-on, EAN 128 (code 128), EAN 13, EAN 13+ Add-on, MSI, 2/5 2-stroke Datalogic, 2/5 3-stroke Matrix, 2/5 5-stroke Industry, Codabar, USD5, Kix and many more!
2-Dimensional	PDF 417, Datamatrix, Maxicode and many more!

PRINT LANGUAGES/EMULATIONS

Standard	HP-LaserJet (PCL5e), Printronix IGP, Printronix Line Printer Plus, Tally MT6xx, IBM Proprinter, Epson FX, MICROPLEX IDOL
Optional	IBM AFP / IPDS, IBM SCS, QMS Code V, QMS Magnum, Kyocera Prescribe, Printronix VGL/PGL, Oasys Express, DEC LN03+, Tektronix 4010/4014, HPGL (7475 A), TIFF (CCITT group 4), Bull MP6090, Fargo, Datamax, Diablo 630, Xerox XES

INTERFACES

Interfaces	10/100 base-T Ethernet, USB, RS232 Serial, IEEE 1284 and Centronics Parallel
------------------	--

Product names mentioned here in are trademarks and/or registered trademarks of their respective companies. All written numbers and specifications in this data sheet are for description purposes only. No promise or guarantee is made as to the accuracy of the numbers or specification provided and furthermore no guarantee is provided that the numbers quoted or specification given will be that of the final product purchased. It remains the duty of the buyer to confirm and prove that the specification provided in the product meets with the buyers needs regarding the buyers specific application and/or installation. Technical specifications may be changed at any time without notice.

